

STINGATOARE DE INCENDIU CU SPUMA TIP SM – PRESURIZATE PERMANENT

Caracterisitici tehnice :

- Valabilitate incarcatura : 3 ani ;
- Durata minima de operare : 12 – 120 secunde ;
- Agent de umplere : AFFF 6% - EL 206 CF
- Gaz propulsor : azot/ nitrogen

Domeniul de utilizare:

- lichide sau solide lichefiabile;
- Inceputul de incendii clasa B (benzina, motorina, petrol, lacuri, vopsele, uleiuri, ceara, parafina, materiale plastice care se topesc usor).
- Inceputul de incendii clasa C (gaze : metan, hidrogen, propan, acetilena).

	Stingator SM6		Stingator SM 9
	Cantitate agent de stingere: 6 kg; Masa: 9,7 kg; Diametru: 152 mm; Inaltime: 555 mm; Focar: 8A/113B; Tip: portativ; Optional: support stingator		Cantitate agent de stingere: 9 kg; Masa: 13,6 kg; Diametru: 152 mm; Inaltime: 710 mm; Focar: 21A/183B; Tip: portativ; Optional: support stingator
	Stingator SM 50		Stingator SM 100
	Cantitate agent de stingere: 50 kg; Masa: 83 kg; Diametru: 300 mm; Inaltime: 1200 mm Focar: A/B; Tip: transportabil;		Cantitate agent de stingere: 100 kg; Masa: 154 kg; Diametru: 420 mm; Inaltime: 1210 mm; Focar: A/B; Tip: transportabil

NOTA: Stingatoarele cu solutie spumanta nu se folosesc asupra echipamentelor!